





SPECIFICATION	0.8	1.0	1.2		
OVERALL LENGHT (mm)	1010	1190	1365		
OVERALL WIDTH (mm)	620				
OVERALL HEIGHT (mm)	880				
TILLING WIDTH (mm/inch)	780	960	1160		
TRACTOR	15+	18+	20+		
LINK TYPE	CAT -				
BLADES (12X44 - 70X7)	16	20	24		
BLADES (12X44 - 70X7)	24	30	36		
TRANSMISSION	GEAR DRIVE				
MAX. WORKING DEPTH (MM)	120				
ROTOR TUBE DIA. (mm)	73				
ROTOR SWING DIA. (mm)	470				
DRIVELINE SAFETY	SHARE BOLT				
WEIGHT (Kg./lbs.)	175 / 385	190 / 418	205 / 452		

The Company Reserves Absolute Rights To Modify The Specifications Of Machine And Components Therein Without Any Prior Notice.

[&]quot;weight Is Including Pto"







MINI ROTAVATOR

INPUT RPM	GEAR BOX	SPUR GEAR 1	SPUR GEAR 2	ROTOR SPEED
540	SINGLE SPEED	-	-	215
	CROWN PINION	13X23		
540	MULTY SPEED	17	18	220
	CROWN PINION	11X18		
	SIDE GEAR	24X43X3	4	

FEATURES

- Great Rigidity of the structure.
- Durable Adjustable Brackets.
- Great Quality of Oil Seal.
- Powder coated-Excellent resistance to corrosion, maintains the
- Machine in just-bought condition for longer period.
- Increase Soil fertility.
- Saving of Fuel and Time.
- Minimum Maintenance.
- Reduce load on tractor.

SUITABLE FOR ALL KIND OF CROPS

OPTIONAL

- Gear Box Single Speed / Multi Speed.
- Strip Type / Full Top Most

SILENT FEATURES

- Heavy Duty Gear Box.
- Shot Blasting process for batter powder coating.
- Boron Steel blades.
- High quality Transmission Parts.

Authorized Dealer



www.fortumexagritech.com

